

# The brain dissociates between different levels of prediction during language comprehension

*Gina R. Kuperberg<sup>1,2,3,4</sup>, Edward W. Wlotko<sup>1,5</sup>, Simone J. Riley<sup>1</sup>, Margarita Zeitlin<sup>1</sup>, Maria Luiza Cuhna-Lima<sup>1</sup>; <sup>1</sup>Tufts University, <sup>2</sup>Massachusetts General Hospital, <sup>3</sup>Athinoula A. Martinos Center for Biomedical Imaging, <sup>4</sup>Harvard Medical School, <sup>5</sup>Moss Rehabilitation Research Institute*

Comprehenders continually use context to generate probabilistic predictions. We asked whether and how these predictions influence neural processing of incoming words. Mini-discourse contexts varied in their constraint for a specific lexical item or event structure. Event-related potentials were recorded to nouns that fulfilled lexical predictions, that violated lexical predictions but were plausible, or that violated the preceding verb's selectional restrictions ('They cautioned the SWIMMERS / TRAINEES/ DRAWER' following a context about lifeguards and sharks). Semantic facilitation was reflected by a selective reduction of the N400 on predictable nouns. Plausible nouns that violated lexical predictions selectively elicited a late anteriorly-distributed positivity, whereas nouns that violated selectional restrictions elicited a late posteriorly-distributed positivity. These dissociable neural signatures of prediction violations at different levels of representation provide support for a hierarchical generative architecture in which bottom-up information is continually evaluated against top-down predictions at multiple levels of representation to support ongoing comprehension.

Primary Keyword = LANGUAGE: Semantic

Secondary Keyword = LANGUAGE: Other